

PAT-NO: JP358117282A
DOCUMENT-IDENTIFIER: JP 58117282 A
TITLE: FUEL OIL COMPOSITION
PUBN-DATE: July 12, 1983

INVENTOR-INFORMATION:

NAME

OKADA, SHIGERU

OTAKI, MAKOTO

YOSHIDA, KOREYUKI

NISHIKIBA, KENJI

NAKADA, YOSHIRO

ASSIGNEE-INFORMATION:

NAME

SANYO CHEM IND LTD

COUNTRY

N/A

APPL-NO: JP57218815

APPL-DATE: December 13, 1982

INT-CL (IPC): C10L001/22

US-CL-CURRENT: 44/417

ABSTRACT:

PURPOSE: To provide a fuel oil compsn. having improved low-temperature flow characteristics and containing a reaction product between a polyisocyanate compd. and a dialkylamine and an ethylene/vinyl acetate copolymer.

CONSTITUTION: A polyisocyanate compd. such as tolylene diisocyanate is reacted with a dialkylamine of the formula (wherein R_{1} and R_{2} are each a $1\sim 26C$ alkyl, the sum of carbon atoms of R_{1} and R_{2} is 18 or more), such as di-n-octadecylamine, in a ratio by equivalent of NCO group to NH group of $1/0.3\sim 1/1.5$ to obtain a urea derivative or a biuret derivative. $0.001\sim 1wt\%$ mixture consisting of said reaction product and a pour point depressant for petroleum oil, such as an ethylene/vinyl acetate copolymer having an MW of $1,000\sim 5,000$ and a vinyl acetate content of $20\sim 50wt\%$ in a weight ratio of $5\sim 95:95\sim 5$, is added to distilled fuel oil such as gasoline, kerosine or fuel oil A.

COPYRIGHT: (C)1983, JPO&Japio